

MITSUBISHI MGS SERIES

DIESEL GENERATOR SET

60Hz/1800 rpm/380V



MGS1200B

POWER RATING (0.8 P.F.)	MODEL CODE
STAND-BY 1265 kW	6S-L50L78
PRIME 1145 kW	6P-L50L78



The photograph is MGS2000B

Voltage Variation

- Standard Voltage 3Phase 4 Wires
380V
- Voltages Available 3Phase 4 Wires
400 and 380V

Note: Outputs for optional voltages may differ from standard output mentioned above.

CONDITIONS & DEFINITIONS

Stand-by: Code: S

Applicable for supplying emergency power at varying load in the event of the normal utility power interruption.

Fuel stop power in accordance with ISO15550, ISO3046/1, JISB8002-1, DIN6271 and BS5514.

Overload: not allowed

Prime: Code: P

Applicable for supplying emergency power at varying load in the event of normal utility power interruption. + 10% overload in accordance with ISO3046/1. Overload power in accordance with ISO15550, ISO3046/1, JIS8002-1, DIN6271 and BS5514.

Conditions:

Engine ratings are based on SAE J1349 standard conditions and also apply at ISO3046/1, DIN6271 & BS5514 standard conditions.

Fuel rates: based on ASTM D975, BS2869 and on fuel oil of 35° API (16°C or 60° F) gravity having a LHV of 42,780 kJ/kg (18,390 Btu/lb.) when used at 29°C (85° F) and weighing 838.9 g/liter (7.001lbs./U.S. gal.).

Note: * For conditions of prime power (P.R.P.) and additional rating requirements, please consult your nearest Mitsubishi MGS dealer.

DIMENSION (Reference Data)

Overall dimensions	L : Length	mm	4595
	W : Width	mm	2155
	H : Height	mm	2495
Total Weight (Dry)		kg	10360
Total Weight (Wet)		kg	11000

MGS SERIES DIESEL ENGINE: MITSUBISHI S12R-PTA-S

V-12, 4 stroke-cycle water-cooled, turbocharged and aftercooled

ENGINE SPECIFICATIONS & TECHNICAL DATA

Bore	mm	170
Stroke	mm	180
Displacement	L	49
Piston speed	m/sec.	10.8
Compression ratio		14
Lubricating oil capacity	L	180
Coolant capacity without radiator	L	125
Coolant pump external resistance	m water	5.0
Coolant pump flow rate	L/min	1850
Cooling fan airflow rate	m ³ /min	1800
Cooling fan air flow restriction	kPa	0.1
Ambient air temperature	°C	40
Allowable exhaust back pressure	kPa	6.0
Exhaust flange size (internal diameter)	mm	300

ENGINE OPERATING DATA

		STAND-BY	PRIME
		1265 kW	1145 kW
Gross Engine Power*	kWm	1336	1210
Brake mean effective pressure	MPa	1.9	1.7
Regenerative absorption	kW	144	144
Noise Level at 1 m (excluding: intake, exhaust & fan)	dB(A)	110	108
Fuel consumption load 100%*	L/hr.	339	307
Fuel consumption load 75%*	L/hr.	262	237
Combustion air inlet flow rate	m ³ /min	116	105
Exhaust gas flow rate	m ³ /min	306	278
Exhaust gas temperature	°C	520	510
Heat rejection to coolant	kW	844	765
Heat rejection to exhaust	kW	1052	949
Heat rejection to atmosphere from engine	kW	101	92
Heat rejection to atmosphere from generator	kW	65	58

* WITH FAN basis.

Deration for engine

Altitude: 2.5% per 300m (1000ft) above 1,500m

Temperature: 2% per 5°C (9° F) above 40°C

ENGINE STANDARD EQUIPMENT

Aftercooler
 Turbocharger filter
 Structure steel base
 Crankcase breather
 Charging alternator
 Lubricating oil cooler
 Fuel filters, full flow paper element
 Fuel transfer pump, gear driven, plunger type
 Electronic type governor
 Jacket water pump, gear driven
 Lubricating oil filter, full flow paper element
 Lubricating oil pump, gear driven
 Exhaust dry manifold
 Radiator, blower fan, fan drive
 Manual shutoff
 24V DC electric starting motor

MGS SERIES 7310 GENERATOR CONTROL PANEL

Type & Design

MGS standard 7310 programmable microprocessor control-automatic start/stop panel, generator breaker control, indicating the operational status and fault conditions; automatically shutting down the engine and indicating the engine failure by means of LCD display and LEDs on the front panel.

Controls & Monitoring

- ◆ Mode selection & start engine button with interlock key switch system
- ◆ Menu navigation button
- ◆ LCD display for: AC amperage-each phase and earth current, AC voltage-each phase and neutral, Frequency Hz, Operation hours run, Lub. Oil pressure, Cooling water temperature, Generator Load kW/kVA/kVar, Generator Load kWh/kVAh/kVarh
- ◆ Operation status LED indicators
- ◆ CB control buttons
- ◆ Mute/Lamp test button
- ◆ Voltage adjuster
- ◆ Speed adjuster
- ◆ Emergency stop pushbutton
- ◆ Provided 5 outputs for status as standard equipment (Programmable 8 outputs available as option)

Safety Shutdown Protection and LED Indicators

High engine temperature, Low oil pressure, Fail to start, Generator Over Speed/Frequency, Generator Under Speed/Frequency
 Generator High Voltage, Generator Low Voltage, Oil pressure sender circuit, Loss of Speed signal, Emergency stop,

Mounting

Fabricated cubicle mounted on individual bracket with anti-vibration isolator

Electrical Design

In accordance with BS EN 60950 Low Voltage Directive, BS EN 61006-2 and 61006-4 EMC Directive. The optional interface can provide real time diagnostic facilities.

Generator Control Panel Description

- | | |
|---|---|
| <ul style="list-style-type: none"> ■ 3 position operation mode control key switch (ACTIVE, PANEL LOCK, STOP/RESET) ■ Manual button ■ Auto button ■ CB open button (Manual only) ■ CB close button (Manual only) ■ Start engine button (Manual only) ■ LCD display accessed by scroll pushbutton <ul style="list-style-type: none"> Generator volts L1-N, L2-N, L3-N Generator volts L1-L2, L2-L3, L3-L1 Generator amps L1, L2, L3 Generator Earth Current Generator Frequency Hz Engine speed RPM Engine oil pressure (PSI & Bar) ■ Visual indicators on LCD display <ul style="list-style-type: none"> Shutdown alarm Warning alarm High coolant temperature Low oil pressure Charge fail Over-speed Under-speed Electrical trip Fail to stop ■ Visual indication alarm and automatically shutdown <ul style="list-style-type: none"> High engine temperature Low oil pressure Fail to start Over-speed High voltage Low voltage ■ Operation status indicated by LED <ul style="list-style-type: none"> Remote start present Generator ready ■ Pre-Programmed Starting Unit <ul style="list-style-type: none"> Automatic start/stop sequence timing and delay systems configured via MS-Windows based software. | <ul style="list-style-type: none"> ■ Stop/Reset button (Manual only) ■ Mute/Lamp test button (Manual only) ■ Voltage adjusting trimmer ■ Speed adjusting trimmer ■ Emergency stop pushbutton Engine cooling water temperature (°C & °F) Battery volts Engine hours run Generator Load kW, kVA, kVar Generator Load kWh, kVAh, kVarh Power Factor Generator Phase Sequence Generator high current Over voltage (AC) Under voltage (AC) Over voltage (DC) Under voltage (DC) Auxiliary indication Auxiliary alarm (warning or shutdown) Common alarm Over frequency Under frequency Over frequency Under frequency Oil pressure sender open circuit Loss of speed signal High Crankcase internal pressure (MGS-C Continuous only) Emergency Stop Lubrication oil filter clogged Electrical trip |
|---|---|

MITSUBISHI MGS SERIES

DIESEL GENERATOR SET

MGS1200B



MGS SERIES AC GENERATOR MODEL: MG-L50L78

Type & Design

MGS original design, single bearing, 4 pole, screen protected, selfexciting, self regulating and brushless with fully connected damper windings, salient pole rotors, A.C. exciter and rotating rectifier unit. Direct coupled to engine and regreaseable bearing, direct drive centrifugal blower.

Enclosure: Drip-proof IP23

Winding System

Standard 6 wire winding provides 3 phase voltage. All windings are impregnated in vacuum pressure impregnated with a special polyester resin.

Overspeed capability: 125% for 2 minutes

Insulation: Class 'H' of IEC

Temperature rise: Class 'H'

Voltage Regulator

Fully sealed, 3 phase RMS sensing AVR with built-in protection against sustained over-excitation. This de-excites the generator after a minimum of 5 seconds.

Voltage regulation: Less than +/- 0.5% from no load to full load at any power factor between 0.8 lagging and 1.0 allowing for a 4% engine speed variation

Voltage adjustment: +/- 6%

Wave form: Less than 5% deviation

AREP and PMI

Electrically isolated from the main alternator stator windings powers AVR - sustaining approx. 300% of short circuit current at the AC generator output terminals for not more than 10 seconds by means of excitation voltage via AVR

Electrical Design

In accordance with, NEMA MG1-22, IEC60034-1, CSA, and ISO8528/3.

Telephone Influence Factor (TIF): Less than 50

Telephone Harmonic factor (THF): Less than 2.5%

Radio interference: Suppression is in line with the provision of VDE Class G and N

Gen Set Option Features

- ENGINE
 - Air Cleaner, paper element dry type
 - Battery Kit
 - Battery Charger
 - Anchor Bolts
- FUEL
 - Fuel Day Service Tank
- COOLING
 - Oversize radiator
 - Heat Exchanger
 - Expansion Tank
 - Jacket Water Heater
 - Removal STD Radiator, Fan & Fan Drive
- LUBRICATION
 - Lub. Oil Priming Pump
- EXHAUST
 - Exhaust Silencer
 - Exhaust Flexible Pipe
- GENERATOR
 - Space Heater
 - 3 phase Sensing Auto Voltage Regulator
 - Power Factor Regulator
- CONTROL PANEL
 - Diesel Generator Integrated Communication Synthesizer (DGICS-MII)
 - Auxiliary Control Panel
 - Remote Monitor Interface
- SWITCHGEAR
 - Circuit Breaker MCCB & ACB
 - Reverse Power Relay

MITSUBISHI HEAVY INDUSTRIES, LTD.

Power Systems Engine Section, Engine Sales Department

16-5, KONAN 2-CHOME, MINATO-KU, TOKYO 108-8215 JAPAN

TEL: 81-3-6716-4771 FAX: 81-3-6716-5854

Mitsubishi Heavy Industries, Ltd. serves for the customers with improved products continually.

Therefore specification and some materials will be changed without notice.

The International System of units (SI) is used in this publication.

